

VT 34 CU control unit brochure



VT 34 CU control unit for DEKRA VT 34/36 PT camera series

Compact control unit for VT 34 PT and VT 36 PT with optionally integrated text inserter

Features

- ▶ Operation of the camera functions directly at the control unit
- ▶ Integrated data display system (optional)
- ▶ Easy handling
- ▶ Light and compact design
- ▶ Additional devices such as monitor and recorder can be connected to the video outputs of the control unit
- ▶ With integrated joystick for pan and tilt function

Applications

- ▶ Intended for the control of VT 34/36 camera series
- ▶ Ideal for temporary inspections

Technical specifications - VT 34 CU control unit

**This document is for general information only,
please consult the system manual for detailed specifications**

Housing	robust ABS
Dimension	174x83x225 mm
Weight	1.2 kg
Video output	CVBS
Connections	camera, keyboard, video
Power consumption	30 W
Input voltage	85-264 V AC / 47-440 Hz
Operating temperature	---
Recording	n/a
Monitor	n/a
Resolution	---
Brightness	---
Contrast	---
Reaction time	---
Optionals	monitor, keyboard
Features	---

* unit in mm



DEKRA Visatec GmbH
 Gewerbepark 7
 87477 Sulzberg/See Germany
 Tel. + 49.8376.9215 0
 info.dvg@dekra.com

dekra-visatec.com