



VT 34 CU *control unit* brochure



VT 34 CU control unit for DEKRA VT 34/36 PT camera series

Compact control unit for VT 34 PT and VT 36 PT with optionally integrated text inserter

Applications

- ▶ Intended for the control of VT 34/36 camera series
- ▶ Ideal for temporary inspections

Features

- ▶ Operation of the camera functions directly at the control unit
- ▶ Integrated data display system (optional)
- ▶ Easy handling
- ▶ Light and compact design
- ▶ Additional devices such as monitor and recorder can be connected to the video outputs of the control unit
- ▶ With integrated joystick for pan and tilt function

Technical specifications - VT 34 CU control unit

This document is for general information only, please consult the system manual for detailed specifications

Housing	robust ABS
Dimension	174x83x225 mm
Weight	1.2 kg
Video output	CVBS
Connections	camera, keyboard, video
Power consumption	30 W
Input voltage	85-264 V AC / 47-440 Hz
Operating temperature	---
Recording	n/a
Monitor	n/a
Resolution	---
Brightness	---
Contrast	---
Reaction time	---
Optionals	monitor, keyboard
Features	---



DEKRA Visatec GmbH
Gewerbepark 7, 87477 Sulzberg/See
Germany
Tel. + 49.8376.9215 0
info.dvg@dekra.com

www.dekra-visatec.com

